Index

4-mile OPDS, 5-14, B-5	air reconnaissance. See reconnaissance, air
4-ton bolster trailer, 2-17, 5-3, 5-4	aligning clamps. See clamp(s), aligning
5-mile pipeline set, 2-1, 5-4	aligning pipelines, 5-11
5-ton, cargo long bed, 2-17	aluminum pipe coupling, 2-3
7 1/2-ton crane, 2-17, 5-9, 5-22	aluminum pipeline facilities, 2-1
12-foot, noncollapsible, discharge, 4-inch hose, 5-16	American Petroleum Institute (API) gravity, 4-1, 4-2
12-foot, noncollapsible, suction, 6-inch hose, 5-16	anchoring pipelines, 5-12
12-foot, suction, 4-inch hose assembly, 5-17	API gravity. See American Petroleum Institute (API) gravity
40-ton crane, 2-17	aqueous film-forming foam (AFFF), 7-9
 50- and 500-foot, lightweight, collapsible, discharge, 6-inch hose, 5-16 350-GPM pump, 7-1 4-inch, single-stage, 7-7 	area, 7-17, 7-18 as a factor in TPT site selection, 7-14 staking out an, 7-10 clearing an, 7-10
600-foot, 6-inch, hose-reel assembly, 5-14 800-GPM mainline pump, 5-19, 5-22	Army Facilities Component System (AFCS), 2-1, 2-5, 5-4, 5-18, 5-19, 7-3
6-inch, 3-stage, 2-10, 4-6	assembling pipe, B-12
3,000-gallon tank, 7-4	assigning crews, 5-8
6,000- and 10,000-pound rough-terrain forklift, 2-17	atmospheric pressure, 4-3, 4-4. See also pressure
10,000-gallon tank, 7-5	
20,000-gallon tank, 7-5	ball valve. See valve(s), ball
50,000-gallon tank, 7-5, 7-25	barrel(s) (bbl), 5-13, 7-1
TPT, optional configuration layout, 7-19	barrel(s) per hour (BPH), 4-4
210,000-gallon tank, 7-6, 7-25	base terminals. See terminals, base
	bbl. See barrel(s) (bbl)
access roads, 7-9, 7-15, 7-18	bending pipe, B-13. See also pipe(s)
adapters double-grooved, 7-17 female, 7-7 male, 7-7	berm(s), 7-13 basin drain, 7-10, 7-25 construction, 7-13 design, 7-20
AFCS. See Army Facilities Component System (AFCS)	Bernoulli equation, A-1 BFTA. See bulk-fuel tank assembly (BFTA)
AFFF. See aqueous film-forming foam (AFFF)	22 200 200 200 200 200 200 200 200 200

bolted coupling, B-1. See also coupling(s)	COMMZ. See communication zone (COMMZ)
BPH. See barrel(s) per hour (BPH)	complexes, 7-3
brass hammers, 5-9, 6-2	compressed-air testing, 5-26
brush hooks, 5-9	computing friction loss, 4-7
bulk-fuel distribution system, 1-1, 3-1 tank assembly (BFTA), 7-6	construction checklist for pump stations, 5-22 materials, 7-22
buried pipe, B-11. See also pipe(s) procedures for, B-12	methods, B-6 staging areas, 3-2, 5-4, 5-7, 5-8 standards, 5-1, B-11
calibration, 5-25	contaminated-fuel, 7-17 module layout, 7-17
cam lock(s), 7-7	continental United States (CONUS), 3-1
camouflage, 3-4	CONUS. See continental United States (CONUS)
capacity, 4-6	conversion formulas, 4-1, A-1
cathodic protection, B-11, B-12	corrosion prevention, B-11
centrifugal pump, 2-10, 7-8. See also pump(s)	couple pipeline, 5-9
cfm. See cubic foot(feet) per minute (cfm)	coupled pipelines, expansion and contraction of,
characteristics of petroleum fuels, 4-1	5-13
check valve. See valve(s), check	coupling(s), 5-2 gaskets, 5-2 procedures, 5-2, 5-11, B-3
CIMIC. See civil military cooperation (CIMIC)	
civil military cooperation (CIMIC), 1-6	replacement, 6-4
clamp(s)	criteria for hydrostatic testing. See hydrostatic testing, criteria for
aligning, B-7 leak-repair, 2-12	cubic foot(feet) per minute (cfm), 2-16
overcoupling-leak, 6-3	culvert
pit-leak, 6-3 repairs, B-22, B-26	installation, 5-17
split-leak, 6-3	pipe, 2-14 size, 5-17
cleaning and packing a pipeline, 5-13	cutting, grooving, and beveling machine, 2-15
cleaning pipe, B-3, B-7	J. C. J.
cleaning rags, 5-9, B-1	Darcy-Weisbach equation, A-2
clearing and leveling a pipeline route, 5-3	deadweight tester, B-3
coating and wrapping pipe, B-12	Defense Fuel Supply Center (DFSC), 3-1
cold bends, B-14, B-15	Defense Logistics Agency (DLA), 3-1
collapsible fabric tanks, 7-4, 7-5, 7-6	design fuel, 4-1
combat heavy engineer battalion, 1-8, 3-1, 7-9	DFSC. See Defense Fuel Supply Center (DFSC)
communications, 5-25	ditching, B-12, B-18
communication zone (COMMZ), 1-4, 1-5	DLA. See Defense Logistics Agency (DLA)
	Little Logorico (Igency (DIM)

double-grooved adapters. See adapters,	FSSPs. See fuel-system supply points (FSSPs)
double-grooved	fuel
drainage, 7-14	-dispensing-assembly layout, 7-17 inhalation and skin contact, 6-3 -system supply points (FSSPs), 1-1
drift pin, 5-9	
dynamic head, 4-3	GAA grease. See general agency agreement (GAA) grease
earthwork, 7-9	gallon(s) per minute (GPM), 1-4, 2-10, 5-16, A-2
elevation, 7-17	gap support structure, 5-4
emergency head capacity, 4-6	gate valve. See valve(s), gate
emergency repairs, B-23	general agency agreement (GAA) grease, 5-9, B-1 mechanic's automotive set, 2-16
ENCOM. See engineer command (ENCOM)	
end caps, 5-9	GPM. See gallon(s) per minute (GPM)
engineer	gravity system, 4-14
branch, 1-8 command (ENCOM), 3-1, 3-3 construction group, 3-1 pipeline construction support company, 3-2 port construction company, 3-2	ground reconnaissance. See reconnaissance, ground
expansion	hand auger, 5-9
and contraction of coupled pipelines, 5-13, B-5	hatchet, 5-9
devices, 5-13	head terminals. See terminals, head
	heavier-weight pipe, 4-17
female adapters. See adapters, female field location of pumping stations, 4-18 reconnaissance. See reconnaissance, field	hose collapsible, dispensing, 1-, 1 1/2-, 2-, and 4-inch, 5-17 connection devices, 7-7
files, B-1, B-25	hose-line systems, 5-13
filling and testing a pipeline, 5-12	hose lines, 7-6, B-27
filling a trench, B-13	host-nation support, 1-5
filter separator, 7-7	hydraulic design, 7-6 drivehead kit, 2-15 gradient triangle, 4-12, 4-15 through 4-17
fire and explosion, 6-2	
fire-suppression equipment, 7-16	
flood pumps, 4-15	hydrostatic testing, 5-23 criteria for, 5-25 using fresh water, 5-23 using fuel, 5-24 using salt water, 5-23
floodlight sets, 7-16	
flow resistance, 4-5	
friction loss, 4-7	ID. See inside diameter (ID)
reducing, 4-9 using double lines, 4-10	impellers, 7-8
using larger pipe, 4-9	-
	improvised structures, 5-19

Inland Petroleum Distribution System (IPDS), 1-7, markings for a pipeline, B-20 2-8, 2-10, 3-2, 4-6 MAWP. See maximum allowable working packaging symbols for the, 2-1 pressure (MAWP) pipes in the, 2-2 inside diameter (ID), 2-2, 4-17 maximum allowable working pressure (MAWP), 2-3, 5-14, 5-15, 5-16. See also pressure inspections, 5-25 measuring pressure. See pressure, measuring installing a coupling, B-4. See also coupling(s), METT-T. See mission, enemy, terrain, troops, procedures and time available (METT-T) intermediate terminals. See terminals, military sealift command (MSC), 3-1 intermediate military-standard (MIL-STD), B-20 International Standards Organization (ISO), 3-2, 5-14 MIL-STD. See military-standard (MIL-STD) IPDS. See Inland Petroleum Distribution System mission, enemy, terrain, troops, and time available (IPDS) (METT-T), 3-2 ISO. See International Standards Organization modular design, 4-11 (ISO) MOGAS. See motor gasoline (MOGAS) modified table of organization and equipment jackrabbit start, 5-9 (MTOE), 5-25 Joint Petroleum Office (JPO), 3-1 motor gasoline (MOGAS), 4-4 JPO. See Joint Petroleum Office (JPO) MSC. See military sealift command (MSC) MSR. See main supply route (MSR) launcher and receiver assembly, 2-8 MTOE. See modified table of organization and equipment (MTOE) lazy board, B-1, B-3 leak-repair clamp. See clamp(s), leak-repair nails, 5-9 liners, 7-23 NATO. See North Atlantic Treaty Organization lizard, B-13 (NATO) local population, as a factor in TPT site selection, NCOIC. See noncommissioned officer in charge 7-9 (NCOIC) locating obstructions, 5-27 nestable culvert material, 5-4 long bolts, 5-9 noncommissioned officer in charge (NCOIC), 5-24 lowering pipe into a trench, B-13 nonemergency repairs, B-23 nonrising-stem valve. See valve(s), nonrising-stem machetes, 5-9 normal head capacity, 4-6 mainline pump-station set, 2-1 North Atlantic Treaty Organization (NATO), 1-6 main supply route (MSR), 3-3 male adapter. See adapter, male obstacle crossing, 5-3, 5-17 map and aerial photograph studies, 3-4 officer in charge (OIC), 5-24 map layout and profile of pipeline route, 3-5

Offshore Petroleum Distribution System (OPDS), 1-8, 5-14, 7-7, B-5	plug valve. See valve(s), plug
	POL. See petroleum, oil, and lubricants (POL)
OIC. See officer in charge (OIC) OPDS. See Offshore Petroleum Distribution System (OPDS)	port support operations, 3-2
	portable facilities, 7-4
operating graphs, 4-6	position welding, B-6
Operations and Training Officer (US Army) (S3),	positioning the pipe, B-4
3-4 operator maintenance, 6-1	pound(s) per square inch (psi), 1-6, 2-8, 4-3, 4-15, 5-15, 5-25, 5-26, A-1
organizational maintenance, 6-1	precautions in trenching, B-12
overcoupling-leak clamp. See clamp(s) overcoupling-leak	pressure, 4-2, 6-2, 6-3 -control valve. See valve(s), pressure-control measuring, 5-23 -reducing stations, 4-17 -reducing valve. See valve(s), pressure-
overhead crossings, 5-18	
pad construction, 5-21, 7-13	reducing -regulating valve. See valve(s), pressure- regulating
permanent repairs, 6-4, B-22	projectiles, 6-2
petroleum, oil, and lubricants (POL), 1-7, 7-9	protective coating, B-19
petroleum terminals, 7-1	psi. See pound(s) per square inch (psi)
pig walkers, 5-25	pump placement, 5-21
pipeline components, 5-2 -construction, grooved-coupling, steel-tubing set, 2-16 jacks, 5-9, B-1 painting, B-19	pump stations, 5-19 locating downstream, 4-19 locating upstream, 4-18 location of, 4-13 spacing of, 4-11
strainer assembly, 2-10 suspension-bridge set, 2-1	pumping pressures, 4-5
valves. See valve(s), pipeline vent assembly, 2-7	pumps, 2-10 flood, 4-15
pipe(s), 2-2, 5-1	pup joints, 2-13, 5-4
ends, 5-2, 5-11 -fitter's general tool kit, 2-16 -fitter's supplemental tool kit, 2-16 fittings, 2-12 friction loss in, 4-7	quartermaster branch, 1-7
-repair accessories, 2-12 replacement, 6-5	rebeveling and cutting, B-7
saw, B-2	reconnaissance
steel, B-1	air, 3-5
weight, 4-17	field, 3-5 ground, 3-5
pit-leak clamp. See clamp(s), pit-leak	reducing friction loss. See friction loss, reducing
placing pipe and valves, 5-8. See also valve(s)	regulating facilities, 7-3
plot plan, 7-9	reverse polarity, B-7

revolution(s) per minute (RPM), 2-5, 7-7	STANAG. See standardization agreement (STANAG)
Reynold's number, A-2	
rising-stem valve. See valve(s), rising-stem	standard pad layout, 5-21
road access, 7-10, 7-15, 7-17, 7-18 as a factor in TPT site selection, 7-9	standardization agreement (STANAG), 1-4 static head, 4-2, 4-17
road and railroad crossings, 5-17	stations on a downgrade, 4-17
roll welding, B-7 route selection	on an upgrade, 4-16 on equal elevations, 4-15
considerations in, 3-3 procedures for, 3-4	steel pipe. See pipe(s), steel
RPM. See revolution(s) per minute (RPM)	steep grades, 4-19
	stream, river, and ravine crossing, 5-18
S&P. See stake and platform (S&P)	supplemental pipeline-pump-station set, 2-16
S3. See Operations and Training Officer (US Army) (S3)	supply levels, 1-5
	support maintenance, 6-1
safety precautions, 6-2	suspension-bridge kits, 5-4
SALMS. See Single-Anchor Leg-Mooring System (SALMS)	suspension bridges, 2-15, 5-18 swabbing and cleaning pipes, B-3
sandbags, 7-22	
saws, 5-9. See also pipe(s), saw	. 11 6
SEE. See small emplacement excavator (SEE)	table of organization and equipment (TOE), 2-14 tactical petroleum terminal (TPT), 1-1, 1-4, 1-6, 3-2, 5-17, 7-1, 7-6, 7-7. See also earthwork; site selection layout, 7-14, 7-16 responsibilities for, 7-1
SG. See specific gravity (SG)	
shovels, 2-16, 5-9 Single-Anchor Leg-Mooring System (SALMS),	
1-8, 5-14	TAMMC. See Theater Army Material Management Center (TAMMC)
criteria, 7-6 layout, 7-14 preparation, 7-10	tank farm(s), 7-1, 7-3 assembly layouts, 7-16
selection, 5-19, 7-9, 7-20	tank pads, 7-13, 7-20
small emplacement excavator (SEE), 1-8, 2-15,	tanker-truck, 7-17
2-17, 5-9, 5-12, B-12	tapping machine, B-2
small pits, B-21	task organization for construction, 5-1
soil conditions, 7-6	temperature, 4-2
specific gravity (SG), 4-1, 4-3	temporary repairs for coupled pipelines, 6-3 for welded pipelines, B-21 terminals. See also tactical petroleum terminal (TPT) base, 7-1
split-leak clamp. See clamp(s), split-leak	
stake and platform (S&P), 5-4	
stake colors, 5-2	
stake pipeline route, 5-2	

```
head, 7-3
                                                                 water availability, as a factor in TPT site section,
   intermediate, 7-3
                                                                    7-9
terrain, 3-4
                                                                 weight density, 4-1
   as a factor in TPT site selection, 7-9
                                                                 welded steel pipeline construction set, 2-16
testing pipeline systems, 5-22
                                                                  welded pipeline systems, B-5
theater army, 1-7, 3-1
                                                                 welded pipelines, B-21
Theater Army Material Management Center
                                                                 welder's steel supplemental pipeline construction
   (TAMMC), 1-7, 3-1
                                                                    set, 2-17
theater of operations (TO), 1-1, 1-4, 1-5, 7-1, B-5
                                                                 welding repairs, B-19
thermal-relief valve. See valve(s), thermal-relief
                                                                 wrenches, 2-16, 5-9
throughput, 4-4
                                                                 wrinkle bends, B-16
tie-ins, B-10
TO. See theater of operations (TO)
                                                                 Z-loop, 5-13
TOE. See table of organization and equipment
   (TOE)
topographic features, 4-11, 7-6
TPT. See tactical petroleum terminal (TPT)
transportation support requirements, 3-2
trenching methods, B-12
U-loop, 5-13
underwater crossings, B-18
US Navy, 1-8
valve(s). See also placing pipe and valves
   ball, 2-8
   check, 2-5, 5-3
   determining location of, 5-3
   gate, 2-3, 5-3
   nonrising-stem, 2-4
   pipeline, 2-3
  plug, 2-5
  pressure-control, 2-8
  pressure-reducing, 2-6, 4-17
  pressure-regulating, 2-6
  rising-stem, 2-3
  thermal-relief, 2-6
  vent, 5-3
vapor pressure, 4-3
vent valves. See valve(s), vent
viscosity, 4-2, 4-6
```